HEATSINK™ PRODUCT HOLDING UNITS FOR BURGER KING

Patented Duke HEATSINK™ Technology

- Extended holding times
- Wraps around bottom and sides of pan to allow for even heat distribution
- It uses no water and eliminates product hot & cold spots
- Improves product quality

Advanced Electronic Controls

- Product quality timers with day part programming and "Universal Red Light – Green Light System"
- Alpha-numeric controls available
- Compatible with ICC Kitchen Minder

Improves Serving Efficiency

- Enhances speed of service
- Increases holding capacity
- Pass through design allows crews to work both sides
- Compartments are easily configured for fried, broiled, grilled or steamed products.

Reduces Costs

- Reduces energy usage
- Increases product yield

Simplified Clean-Up and Maintenance

- Easy to clean - just remove pans & covers and wipe down
- No cracks or crevices to collect debris
- No doors, latches or hinges to break

Your Solutions Partner

Shipping Weight: 141lbs / 64kg		Width		Height		Depth	
Available Models	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-42SB1,SB2, MB1, MB2	120V, 13.3A, 1600W, 50/60Hz	21	53.3	22	55.9	16	40.6
FWM3-42SB1,SB2, MB1, MB2	208V, 11.5A, 2400W, 50/60Hz	21	53.3	22	55.9	16	40.6
FWM3-42SB1,SB2, MB1, MB2	230V, 10.4A, 24200W, 50/60Hz	21	53.3	22	55.9	16	40.6
FWM3-42SB1,SB2, MB1, MB2	240V, 10.0A, 2400W, 50/60Hz	21	53.3	22	55.9	16	40.6

Shipping Weight: 165lbs / 75kg		Width		Height		Depth	
Available Models	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-34MB1, FWM3-34MB1A	208v, 11.6A, 2400W, 50/60Hz	37	94.0	17	43.0	16	40.6
FWM3-34MB1, FWM3-34MB1A	230v, 10.4A, 2400W, 50/60Hz	37	94.0	17	43.0	16	40.6

Shipping Weight: 91lbs / 41kg		Width		Height		Depth	
Available Models	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-22SB1,SB2, MB1, MB2	120V, 6.7A, 800W, 50/60Hz	21	53.3	12	30.5	16	40.6
FWM3-22SB1,SB2, MB1, MB2	208V, 5.8A, 1200W, 50/60Hz	21	53.3	12	30.5	16	40.6
FWM3-22SB1,SB2, MB1, MB2	230V, 5.2A, 1200W, 50/60Hz	21	53.3	12	30.5	16	40.6
FWM3-22SB1,SB2, MB1, MB2	240V, 5.0A, 1200W, 50/60Hz	21	53.3	12	30.5	16	40.6

Shipping Weight: 141lbs / 64kg		Width		Height		Depth	
Available Models	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-24SB1,SB2, MB1, MB2	120V, 6.7A, 1600W, 50/60Hz	37	94.0	12	30.5	16	40.6
FWM3-24SB1,SB2, MB1, MB2	208V, 5.8A, 2400W, 50/60Hz	37	94.0	12	30.5	16	40.6
FWM3-24SB1,SB2, MB1, MB2	230V, 5.2A, 2400W, 50/60Hz	37	94.0	12	30.5	16	40.6
FWM3-24SB1,SB2, MB1, MB2	240V, 5.0A, 2400W, 50/60Hz	37	94.0	12	30.5	16	40.6

Shipping Weight: 113lbs / 51kg		Width		Height		Depth	
Available Models	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-23SB1,SB2, MB1, MB2	120V, 10.0A, 1200W, 50/60Hz	29	73.7	12	30.5	16	40.6
FWM3-23SB1,SB2, MB1, MB2	208V, 8.7A, 1800W, 50/60Hz	29	73.7	12	30.5	16	40.6
FWM3-23SB1,SB2, MB1, MB2	230V, 7.8A, 1800W, 50/60Hz	29	73.7	12	30.5	16	40.6
FWM3-23SB1,SB2, MB1, MB2	240V, 7.5A, 1800W, 50/60Hz	29	73.7	12	30.5	16	40.6

Duke Manufacturing Co.
2305 N. Broadway
St. Louis, MO 63102
Toll Free: 800-735-3853
Phone: 314-231-1130
www.dukemfg.com

Order online at
www.TheBetterWayToBroil.com
or call 800-735-3853, ext. 260
or fax 314-231-5074

For inquiry or order
assistance contact:
Bob Booker
800-735-3853

© Duke Manufacturing Co. 2009
BKPHUSS09